

# Lebus<sup>®</sup> Snatch Blocks



**Fatigue Rated**



**SEE APPLICATION AND WARNING INFORMATION**

Para Español: [www.thecrosbygroup.com](http://www.thecrosbygroup.com)

On Pages 342-349

## L-160 Series Heavy Duty Snatch Blocks

- Hook is Forged Alloy Steel — Quenched and Tempered.
- Designed for fast, efficient line changes.
- All parts are forged.
- Beaded side plate prevents rope from jamming.
- Available with hook, shackle or tailboard (pin only).
- Can be furnished with hook latch.
- Blocks furnished with dual rated wireline sheaves.
- Fatigue Rated.



**L-5-H**



**L-5-S**



**L-5-T**

Block No.	Bearing Code	L-160 Stock No.	Fitting	Sheave Diam. (mm)	Working Load Limit (t)*	Wire Rope Size (mm)	Weight Each (kg.)	Rep. Sheave Stock No.	Rep. Latch Stock No.
L-5-H	BB	599506	Hook	127	6	10-13	6.94	592095	1096468
L-5-H	RB	599515	Hook	127	6	10-13	6.94	592157	1096468
L-5-S	BB	599524	Shackle	127	6	10-13	6.80	592095	-
L-5-S	RB	599533	Shackle	127	6	10-13	6.80	592157	-
L-5-T	BB	599542	Tailboard	127	6	10-13	4.54	592095	-
L-5-T	RB	599551	Tailboard	127	6	10-13	4.54	592157	-
L-6-H	BB	599560	Hook	149	12	16-19	14.4	592175	1096609
L-6-H	RB	599579	Hook	149	12	16-19	14.4	592255	1096609
L-6-S	BB	599588	Shackle	149	12	16-19	13.6	592175	-
L-6-S	RB	599597	Shackle	149	12	16-19	13.6	592255	-
L-6-T	BB	599604	Tailboard	149	12	16-19	8.07	592175	-
L-6-T	RB	599613	Tailboard	149	12	16-19	8.07	592255	-

\* Ultimate Load is 4 times the Working Load Limit.

NOTE: When ordering, please specify: size, block number, hook or shackle, bronze bushed or roller bearing and wire rope size.