

McKissick® Snatch Blocks

Fatigue Rated®

SEE APPLICATION AND WARNING INFORMATION
 Para Español: www.thecrosbygroup.com On Pages 342-349

416, 417 & 402 ALLOY SNATCH BLOCKS



**416
WITH HOOK**



**417
WITH SHACKLE**



**402
TAIL BOARD**

All Alloy Snatch Blocks

- Entire block made from heat treated alloy steel. Use of heat treated alloy gives block only 60% of the weight of blocks of comparable capacities.
- Available with a bronze bushed or roller bearing sheaves.
- Easy opening feature of "Champion" blocks retained.
- Hook and shackle assemblies can be interchanged.
- Pressure lube fittings.
- Can be furnished with hook latch.
- Blocks furnished with dual rated wireline sheaves.
- Fatigue Rated.
- All sizes are **RFID EQUIPPED**.



Sheave Diameter (mm)	Bearing Code	Stock No.			Wire Rope Size (mm) †	Working Load Limit (t)*	Weight Each (kg.)			Rep. Sheave Stock No.	Rep. Latch Stock No.
		416 Alloy with Hook	417 Alloy with Shackle	402 Alloy Tail Board			416 Alloy with Hook	417 Alloy with Shackle	402 Alloy Tail Board		
152	BB	193427	168972	179238	19-22	12	11.8	12.20	6.80	460824	1096609
152	RB	193472	193757	179283	19-22	12	11.8	12.20	6.80	472679	1096609
203	BB	193490	168990	179318	19-22	12	15.0	15.40	9.50	461173	1096609
203	RB	193542	193819	179363	19-22	12	15.0	15.40	9.50	473286	1096609
254	BB	193613	193882	179434	19-22	12	18.6	19.10	13.20	461814	1096609
254	RB	193677	193935	179498	19-22	12	18.6	19.10	13.20	473785	1096609

* Ultimate Load is 4 times the Working Load Limit.
 † May be furnished in other wire rope sizes.

NOTE: When ordering, please specify: size, block number, hook or shackle, bronze bushed or roller bearing and wire rope size.

McKissick
Blocks