

McKissick® Snatch Blocks

Fatigue Rated



SEE APPLICATION AND WARNING INFORMATION

Para Español: www.thecrosbygroup.com

On Pages 342-349

420, 421 & 406 SNATCH BLOCKS



**420
WITH HOOK**



**421
WITH SHACKLE**



**406
TAIL BOARD**

Champion

- Hooks and side plates are forged alloy steel and heat treated.
- Shackles and yokes are forged and heat treated steel.
- All parts are forged.
- Side plates are designed to eliminate possibility of rope jamming.
- Can be furnished with bronze bushings or sealed roller bearings.
- Opening feature permits insertion of rope while block is suspended from gin-pole.
- Can be furnished with S-4320 hook latch.
- Pressure lube fittings.
- Hook and shackle assemblies can be interchanged.
- Blocks furnished with dual rated wireline sheaves.
- Fatigue Rated.
- All sizes are **RFID EQUIPPED**.



Sheave Diam. (in.)	Bearing Code	Stock No.			Wire Rope Size (mm) †	Working Load Limit (t)*	Weight Each (kg.)			Rep. Sheave Stock No.	Rep. Latch Stock No.
		420 with Hook	421 with Shackle	406 Tail Board			420 with Hook	421 with Shackle	406 Tail Board		
6	BB	169374	169481	167973	19-22	12	18.1	21.8	10.9	460940	1096609
6	RB	169392	204120	167982	19-22	12	18.1	21.8	10.9	473035	1096609
8	BB	169418	169515	167991	19-22	15	23.1	25.9	13.6	461360	1096609
8	RB	169445	204193	168008	19-22	15	23.1	25.9	13.6	473534	1096609
10	BB	110221	110720	103186	19-22	15	28.6	31.3	19.1	462001	1096609
10	RB	110258	110757	103202	19-22	15	28.6	31.3	19.1	474025	1096609

* Ultimate Load is 4 times the Working Load Limit.
† May be furnished in other Wire Rope sizes.

NOTE: When ordering, please specify: size, block number, hook or shackle, bronze bushed or roller bearing and wire rope size.