

Western Standard Steel Blocks

SEE APPLICATION AND WARNING INFORMATION
 Para Español: www.thecrosbygroup.com On Pages 342-349



HS-262 DOUBLE

Loose Side Hooks with Latch For Manila Rope

- Laser cut side plates
- Grade 5 bolts secured with lock washers and staked nuts.
- Bronze bushed sheaves with larger bearing diameter for extended block life.

Block Size (in.)	Fitting	Manila Rope Size (mm)	Sheave Size (mm)			261 B Stock No.	262 B Stock No.	263 B Stock No.	Working Load Limit (t)*			Weight Each (kg.)		
			Outside Diam.	Rim Thickness	Center Pin Dia.				261 Single	262 Double	263 Triple	261 Single	262 Double	263 Triple
4	HS	13	57.0	16.0	9.65	666826	666229	667228	.41	.64	.82	.63	1.46	1.47
5	HS	16	76.0	19.1	12.7	666844	666247	-	.54	.82	-	1.02	1.76	-
6	HS	19	89.0	25.4	15.8	666862	666265	-	.82	1.13	-	1.70	2.72	-
8	HS	22-26	121	28.7	19.1	666906	666309	667308	1.27	1.72	2.18	3.23	4.88	6.69

* Ultimate Load is 3 times the Working Load Limit.



N-411-B

Blocks for Synthetic Fiber Rope with loose swivel hooks

- These blocks are built to carry the increased loads of synthetic fiber ropes.
- All hooks are heat-treated alloy steel.
- You can now use a smaller size rope, and in turn, a smaller block, providing capacities which were previously not possible.

Block Size (in.)	Fitting	411 B* Stock No.	412 B* Stock No.	413 B* Stock No.
4	S	755105	755301	755506
6	S	755123	755329	755524
4	N	757103	757309	757504
6	N	757121	757327	757522

* Bearing Code: B-Self Lubricating Bronze Bushed

Block Size (in.)	Fitting	Sheave Size (mm)			Synthetic Rope Size (mm)	Working Load Limit (t)*			Weight Each (kg.)		
		Outside Diameter	Rim Thickness	Center Pin Dia.		Single	Double	Triple	Single	Double	Triple
4	S	57.2	15.8	9.65	13	.90	1.36	1.36	1.36	1.81	2.72
6	S	89.0	25.4	12.7	19	1.36	3.18	3.63	2.83	4.54	6.35
4	N	57.2	15.8	9.65	13	.91	1.36	1.36	1.36	1.81	2.72
6	N	89.0	25.4	12.7	19	1.36	1.81	2.72	2.83	4.54	6.35

* Ultimate Load is 4 times the Working Load Limit.



HW-261B

HW-261 HW-262 5" Steel Blocks

- For 10 mm diameter wire cable.
- Sheave Size: 76 x 19 x 10mm.

Block Size (in.)	Fitting	Block Stock No.	Catalog No.	Bearing Type	Wire Rope Size (mm)	Working Load Limit (t)*	Weight Each (kg)
5	H	665444	HW261-B	Bronze Bushed	10	.54	.91
5	H	665462	HW262-B	Bronze Bushed	10	.82	1.81

* Ultimate Load is 3 times the Working Load Limit.



HW-262B