


Western Blocks for Manila Rope


SEE APPLICATION AND WARNING INFORMATION
 Para Español: www.thecrosbygroup.com On Pages 342-349



T-350-C

Gin Blocks for Manila Rope

- For light hoisting by Roofers and Contractors.
- Furnished with drop forged swivel latch hooks.

Block Size (in.)	Fitting	Gin Block Stock No.			Sheave Size (mm)			Manila Rope Size (mm)	Working Load Limit (t)*	Weight Each (kg)
		T-350-B	T-350-R	T-350-C	Outside Diam.	Rim Thickness	Bearing Diam.			
8	T	710403	710207	710001	203	31.8	19.1	22	.45	4.10
10	T	710421	710225	710029	254	31.8	22.4	26	.45	5.45
12	T	710449	710243	710047	305	35.1	22.4	26	.45	7.25

* Ultimate Load is 3 times the Working Load Limit.

Bearing Code: B-Self Lubricating Bronze Bushed, R-Roller Bearing, C-Common Iron

Painter's Supply Blocks for Manila Rope



**HS-130-B
SINGLE**

- Furnished in Bronze Bushed.
- For 3/4" (19mm) Manila Rope.
- Steel Parts are Galvanized.
- Furnished with Loose Side Hooks with Latch or Shackle.

Block Size (in.)	Fitting	Single Sheave Blocks	Double Sheave Blocks	
		HS-130 B* Stock No.	HS-135 B* Stock No.	P-135 B* Stock No.
6	HS	601236	631034	-
6	HS	-	-	8004829

* Bearing Code: B-Self Lubricating Bronze Bushed

Block Size (in.)	Sheave Size (mm)			Manila Rope Size (mm)	Resultant Working Load Limit (t)*		Weight Each (kg)	
	Outside Diam.	Rim Thickness	Center Pin Dia.		130 Single	135 Double	130 Single	135 Double
6	89.0	25.4	19.1	19	.82	1.13	2.27	4.54

* Ultimate Load is 4 times the Resultant Working Load Limit.