


Western Cargo Hoisting Blocks



**SEE APPLICATION AND
WARNING INFORMATION**

Para Español: www.thecrosbygroup.com

On Pages 342-349



**E-566
W/DRILLED
SWIVEL EYE**

566 Cargo Hoisting Blocks

- Block is galvanized.
- Blocks 356mm and larger have flame-hardened Roll Forged™ sheaves that assure greater wire life.
- Roll Forged™ sheave is fitted closely into mortise of shell so wire cannot jam between sheave and shell.
- Available for 19mm or 25mm wire.
- Block is fitted with tapered roller bearings which take both load and side thrusts and hold sheave central so it cannot chafe or wear on the sides.
- Tapered Roller bearing with neoprene seals and stainless steel center pin, provide long life and trouble-free service.
- Stainless steel center pin has recessed nuts with lock washers.
- Swivel fitting has permanently sealed thrust bearing.
- Pressure lubrication fittings are standard on both center pin and swivel.
- Individually Proof Tested at 4 times Working Load or 2 times Resultant Load.
- A.B.S. recognized load test certificates are furnished.
- The Working Load for Cargo hoisting blocks is the line pull.



**J-566
W/OBLONG
SWIVEL EYE**

Sheave Size (mm)	Block No.	566 Stock No.	Working Load Limit (t)*	Wire Rope Size (mm)	Weight Each (kg)
305	E-566	775003	4.54	19	43.1
305	J-566	775209	4.54	19	43.1
305	G-566	775405	4.54	19	43.1
305	K-566	775600	4.54	19	43.1
305	QG-566	775806	4.54	19	43.1
305	QK-566	776002	4.54	19	43.1
356	E-566	775058	9.07	19	45.4
356	J-566	775254	9.07	19	45.4
356	QG-566	775450	9.07	19	45.4
356	QK-566	775655	9.07	19	45.4
356	PG-566	775851	9.07	19	45.4
356	PK-566	776057	9.07	19	45.4
356	E-566	775067	9.07	25	45.4
356	J-566	775263	9.07	25	45.4
356	QG-566	775469	9.07	25	45.4
356	QK-566	775664	9.07	25	45.4
356	PG-566	775860	9.07	25	45.4
356	PK-566	776066	9.07	25	45.4
406	E-566	776609	9.07	19	59
406	J-566	776672	9.07	19	59
406	QG-566	776681	9.07	19	59
406	QK-566	776690	9.07	19	59
406	PG-566	776707	9.07	19	59
406	PK-566	776716	9.07	19	59
406	E-566	752956	9.07	25	59
406	J-566	752965	9.07	25	59
406	QG-566	752974	9.07	25	59
406	QK-566	752983	9.07	25	59
406	PG-566	752992	9.07	25	59
406	PK-566	753009	9.07	25	59

* Working Load equals maximum single line pull. Resultant Load equals 2 times single line pull. Ultimate Load equals 5 times the Resultant Load.