

# High Performance Sling Connector


**Sling Saver** Load Rated **"QT"**  
QUENCHED & TEMPERED

**S-237**



High Performance Sling Connector is designed to connect High Performance Synthetic Slings of all materials.

- Capacities available:
  - Working Load Limit (5 to 1): 2,268 through 27,215 kg.
  - Sling Body Widths: 51mm through 152mm.
- Allows easy connection to master links or eye hooks, and is ideal for bridles.
- Increased radius of bow gives wider sling bearing surface resulting in an increased area for load distribution, thus:
  - Increasing Synthetic Sling efficiency as compared to master links, shackle bows and conventional eye hooks. This allows 100% of the slings rated Working Load Limit to be achieved.
  - Allows better load distribution on internal fibers.




S-237

**S-238**



- All Alloy Construction
- Design Factor of 5 to 1.
- Individually Proof Tested at 2.5 times the Working Load Limit.
- Each connector has a Product Identification Code (PIC) for material traceability, along with a frame size, and the name Crosby and USA in raised letters.



S-238

## S-237 High Performance Sling Connector

Working Load Limit		S-237 Web to Lok-A-Loy Assy. Stock No.	Frame No.	Nominal Sling Body Width (mm)	Lok-A-Loy Size	Weight Each (kg)	Dimensions (mm)										
4:1 (kg)*	5:1 (kg)						A	B	C	E	G	H	L	N	R	S	W
2835	2268	1020695	5	51	10	.52	22.4	36.1	50.8	80.8	25.4	20.3	107	26.4	74.2	12.2	35.1
5670	4536	1020704	10	76	16	1.34	36.1	38.6	69.9	105	31.8	24.9	144	43.4	100	19.0	44.5
8505	6804	1020713	15	76	20	2.15	41.4	40.1	69.9	111	35.1	27.9	165	51.8	113	23.6	47.8
14175	11340	1020722	25	102	22	3.90	50.8	59.2	95.3	152	44.5	35.8	202	57.7	140	26.9	57.2
17010	13607	1020731	30	102	22	4.19	50.8	55.9	95.3	157	44.5	35.8	199	57.7	137	26.9	60.5
22680	18145	1020740	40	127	25	7.1	57.2	73.9	121	184	57.2	45.2	240	62.0	164	31.0	78.5
34020	27215	1020759	60	152	32	11.8	65.0	85.3	146	232	58.7	47.2	281	78.0	196	38.1	80.3

\* Maximum Proof Load is 2 times the Working Load Limit at 4:1 design factor. Minimum Ultimate strength is 5 times the Working Load Limit.

Crosby Sling Saver hardware meets the requirements for minimum stock diameter or thickness, and effective contact width shown in the Recommended Standards Specification for Synthetic Polyester Round Slings by the Web Sling & Tie Down Association. WSTDA-RS1 (revised 2001)

## S-238 High Performance Sling Connector

Working Load Limit (kg)	S-238 Web to Web Assembly Stock No.	Frame No.	Nominal Sling Body Width (mm)	Lok-A-Loy Size (mm)	Weight Each (kg)	Dimensions (mm)										
						A	B	C	E	G	H	K	M	W		
2268	1020415	5	50.8	10	.73	22.4	36.1	50.8	80.8	25.4	20.3	124	83.8	35.1		
4536	1020423	10	76.2	16	1.50	36.1	38.6	69.9	105	31.8	24.9	145	95.5	44.5		
6804	1020432	15	76.2	20	2.22	41.4	40.1	69.9	111	35.1	27.9	156	101	47.8		
11340	1020441	25	102	22	4.58	50.8	59.2	95.3	152	44.5	35.8	213	142	57.2		
13608	1020450	30	102	22	5.17	50.8	55.9	95.3	157	44.5	35.8	207	135	60.5		
18144	1020469	40	127	25	9.39	57.2	73.9	121	184	57.2	45.2	266	176	78.5		
27216	1020478	60	152	32	14.5	65.0	85.3	146	232	58.7	47.2	298	203	80.3		

\* Maximum Proof Load is 2.5 times the Working Load Limit. Minimum Ultimate strength is 5 times the Working Load Limit.

Crosby Sling Saver hardware meets the requirements for minimum stock diameter or thickness, and effective contact width shown in the Recommended Standards Specification for Synthetic Polyester Round Slings by the Web Sling & Tie Down Association. WSTDA-RS1 (revised 2001)